

MAKERS OF WIDE RANGE OF OSCILLOSCOPES, D. V. M. S, D. P. M. S, SIGNAL GENERATORS, F. E. T. INPUT MULTIMETERS, POWER SUPPLIES, AND OTHER CUSTOM MADE ELECTRONIC INSTRUMENTS.



ISO 9001 : 2000




SPECIFICATIONS

LED Fluorescent Lights

Features:

- Options Available: T5, T8 and T10
- Beam angle: 120°
- Base type: T5/T8/T10 Bi-pin
- Light source: 5 mm Straw-Hat LEDs/SMD LEDs
- CRI: 75
- Life Time: 50,000 Hours




■ ■ MAKERS OF WIDE
RANGE OF OSCILLO
SCOPES, ■ ■ D. V. M. S.
D. P. M. S. ■ ■ SIGNAL
GENERATORS, F. E. T.
INPUT MULTIMETERS
■ ■ POWER SUPPLIES,
AND OTHER CUSTOM
MADE ELECTRONIC
INSTRUMENTS. ■ ■ ■

- **Input Voltage: 100-264 V AC**
- **Working Temperature: Up to 40 degrees Celsius**
- **Storage Temperature: -40~60 degrees Celsius**
- **Luminous Decay: 3%-5%/1000 Hrs.**
- **No UV & IR radiation**
- **Clear/Milky PC tube housing, with bi-pin socket at both sides (PMMA housing optional)**
- **Length: 600mm & 1200mm (300mm/900mm/1500mm optional)**
- **Quick mounting brackets provide ease of installation and lower installation costs**
- **Warranty: 1 Year**
- **Packing: 60 pcs per carton.**

Applications:

- **Bus, shuttle, railcar passenger interiors**
- **Uninterrupted emergency lighting**
- **Focused reading and Task lighting**
- **Interior design usage**
- **Retail store displays**
- **Closet illumination**
- **Bay lighting**
- **Marine recreation applications**
- **Concealed accent lighting**
- **Edge lighting**
- **Under counter lighting**
- **Cubicle, workbench lighting**
- **Recreational vehicle interiors**




■ ■ MAKERS OF WIDE
 RANGE OF OSCILLO
 SCOPES. ■ ■ D. V. M. S.
 D. P. M. S. ■ ■ SIGNAL
 GENERATORS. F. E. T.
 INPUT MULTIMETERS
 ■ ■ POWER SUPPLIES,
 AND OTHER CUSTOM
 MADE ELECTRONIC
 INSTRUMENTS. ■ ■ ■

Ø Specifications of LED Tube Light:

Model No.	T5				T8				T10			
Length (mm)	600mm		1200mm		600mm		1200mm		600mm		1200mm	
Diameter (mm)	16		16		25		25		30		30	
Color	Warm White / Pure White / Cool White (WW / PW / CW)											
Color Temperature (K)	2700K – 9600K											
5 mm LED Quantity (PCS)	60		120		144		288		144		288	
Voltage (V)	12 – 24VDC				100 – 264VAC				100 – 264VAC			
Efficiency	≥ 90 (Approx.)											
Wattage (W)	3		6		8		16		8		16	
Light output (Lumens)	N	H	N	H	N	H	N	H	N	H	N	H
	250	1020	496	2040	596	2448	1192	4896	596	2448	1192	4896

N- Normal, H- High

Note: Specific customer requirement will be catered separately.



MAKERS OF WIDE RANGE OF OSCILLOSCOPES, D. V. M. S, D. P. M. S, SIGNAL GENERATORS, F. E. T. INPUT MULTIMETERS, POWER SUPPLIES, AND OTHER CUSTOM MADE ELECTRONIC INSTRUMENTS.

Ø Ordering Code:

