

MAKERS OF WIDE RANGE OF OSCILLOSCOPES, D. V. M. S. D. P. M. S. SIGNAL GENERATORS, F. E. T. INPUT MULTIMETERS, POWER SUPPLIES, AND OTHER CUSTOM MADE ELECTRONIC INSTRUMENTS.




ISO 9001 : 2000

Ø Spot Light Specifications:

Colour of Light	White (Warm White/Cool White) Superior Colour Quality
Appearance	Standard Bulb with E27, B22 or E26 Bases (Other Options available as per user demand)
Material	Transparent/Opaque Shell in PC/PMMA (Glass shell can be made available on customer request)
RoHS Compliance	No Mercury (Hg) Or Lead (Pb) used
Emissions	No UV/IR Radiations
Visual Effect	No flicker and Clear Light with 100% Shell Transparency
Heat Effect	Low Heat Dissipation & hence Low Working Temperatures
Life Span	Long life time (50,000 Hrs.) against conventional incandescent lamp
Energy Utilization	Less Energy Consumption
Compatibility	4W can replace up to 40 W filament bulb

Ø Spot Light Product Features:

Colour of Light	White (CCT= 2800K to 9600K)
LED Type	Super Bright 5 mm Round Straw Hat LEDs/ High Power LED
LED Qty.	30 Nos./ 60 Nos./ 5 Nos. (High Power)
Shell Size	φ=70 mm to 100 mm (Dia.) depending upon type
Appearance	Standard Round Bulb with E27, B22 or E26 Base
Material	Transparent/Milky White PC Shell
Power Consumption	2 Watts to 5 Watts
Working Efficiency	> 90%
Life Time	50,000 Hrs.
Luminous Decay	3% - 5% per 1000 Hrs.
Light Output	125 lm to 825 lm as per the type




■ ■ MAKERS OF WIDE
RANGE OF OSCILLO
SCOPES. ■ ■ D. V. M. S.
D. P. M. S. ■ ■ SIGNAL
GENERATORS. F. E. T.
INPUT MULTIMETERS
■ ■ POWER SUPPLIES,
AND OTHER CUSTOM
MADE ELECTRONIC
INSTRUMENTS. ■ ■ ■



- Moderate Size High Bright Energy Saving Lamp
- Reliable Solid State & Long Lasting CC LED Driver
- Choice of Different Bases
- Special Mounting Plate With Equally-spaced LEDs In An Aesthetic Arrangement For Even Light Distribution & Heat Dissipation

Type:	SL080-N / SL080-H
No. Of LEDs:	30 Nos. 5mm Straw Hat
Voltage:	90-265 VAC, 50-60 Hz. input
Power Consumption:	<= 2Watts
Lumens:	125 Lumens for SL080-N 415 Lumens for SL080-H
Lux:	92 @ 1 mtr. on std. White Light Photo Detector (for SL080-H)
CCT:	Warm / Cool White
LED Viewing Angle:	120°
Dimensions:	φ 80*135 mm
Packing:	10 In 1 Carton




■■ MAKERS OF WIDE RANGE OF OSCILLOSCOPES. ■■ D. V. M. S. D. P. M. S. ■■ SIGNAL GENERATORS. F. E. T. INPUT MULTIMETERS ■■ POWER SUPPLIES, AND OTHER CUSTOM MADE ELECTRONIC INSTRUMENTS. ■■ ■■



- Moderate Size High Bright Energy Saving Lamp
- Reliable Solid State & Long Lasting CC LED Driver
- Choice of Different Bases
- Special Mounting Plate With Equally-spaced LEDs In An Aesthetic Arrangement For Even Light Distribution & Heat Dissipation

Type:	SL100-N / SL100-H
No. Of LEDs:	60 Nos. 5mm Straw Hat
Voltage:	90-265 VAC, 50-60 Hz. input
Power Consumption:	<= 4Watts
Lumens:	250 Lumens for SL100-N 825 Lumens for SL100-H
Lux:	Better Than 200 @ 1 mtr. on std. White Light Photo Detector (for SL100-H)
CCT:	Warm / Cool White
LED Viewing Angle:	120°
Dimensions:	φ 100*135 mm
Packing:	5 In 1 Carton




MAKERS OF WIDE RANGE OF OSCILLOSCOPES, D. V. M. S. D. P. M. S. SIGNAL GENERATORS, F. E. T. INPUT MULTIMETERS, POWER SUPPLIES, AND OTHER CUSTOM MADE ELECTRONIC INSTRUMENTS.



- Moderate Size High Bright Energy Saving Lamp
- Reliable Solid State & Long Lasting CC LED Driver
- Choice of Different Bases
- Special Mounting Plate With Equally-spaced LEDs In An Aesthetic Arrangement For Even Light Distribution & Heat Dissipation

Type:	SL045-N / SL045-H
No. Of LEDs:	30 Nos. 5mm Straw Hat
Voltage:	90-265 VAC, 50-60 Hz. input
Power Consumption:	<= 2Watts
Lumens:	125 Lumens for SL045-N 415 Lumens for SL045-H
Lux:	Better Than 90 @ 1 mtr. on std. White Light Photo Detector (for SL045-H)
CCT:	Warm / Cool White
LED Viewing Angle:	120°
Dimensions:	ƒ 45*80 mm
Packing:	10 In 1 Carton




MAKERS OF WIDE RANGE OF OSCILLOSCOPES, D. V. M. S. D. P. M. S. SIGNAL GENERATORS, F. E. T. INPUT MULTIMETERS, POWER SUPPLIES, AND OTHER CUSTOM MADE ELECTRONIC INSTRUMENTS.



- Moderate Size High Power Energy Saving Lamp
- Reliable Solid State & Long Lasting CC LED Driver
- Choice of Different Bases
- Special Heat Dissipating Plate With Equally-spaced 1W LEDs In An Aesthetic Arrangement For Even Light Distribution

Type:	SL070-H
No. Of LEDs:	5 x 1W High Power LEDs
Voltage:	90-265 VAC, 50-60 Hz. input
Power Consumption:	<= 5Watts
Lumens:	425 Lm
Lux:	Approx. 100 @ 1 mtr. on std. White Light Photo Detector
CCT:	Warm / Cool White
LED Viewing Angle:	120°
Dimensions:	f 70*140 mm
Packing:	5 In 1 Carton



■ ■ ■ MAKERS OF WIDE
 RANGE OF OSCILLO
 SCOPES. ■ ■ ■ D. V. M. S.
 D. P. M. S. ■ ■ ■ SIGNAL
 GENERATORS. F. E. T.
 INPUT MULTIMETERS
 ■ ■ ■ POWER SUPPLIES,
 AND OTHER CUSTOM
 MADE ELECTRONIC
 INSTRUMENTS. ■ ■ ■

Ordering Code:

