

■ ■ ■ MAKERS OF WIDE
RANGE OF OSCILLO
SCOPES. ■ ■ ■ D. V. M. S.
D. P. M. S. ■ ■ ■ SIGNAL
GENERATORS. F. E. T.
INPUT MULTIMETERS
■ ■ ■ POWER SUPPLIES,
AND OTHER CUSTOM
MADE ELECTRONIC
INSTRUMENTS. ■ ■ ■




ISO 9001 : 2000

Ø **SIGNAL GENERATOR/FUNCTION GENERATOR:**



Ø ***Salient Features:***

1. Sine/square & single-shot square wave forms available in one model.
2. Waveform distortion is better than 1% & electronically regulated output amplitude.
3. Useful for digital IC & microprocessor bit testing.
4. In-built DC regulated power supply to enhance the versatility of instrument.



■ ■ ■ MAKERS OF WIDE
 RANGE OF OSCILLO
 SCOPES. ■ ■ ■ D. V. M. S.
 D. P. M. S. ■ ■ ■ SIGNAL
 GENERATORS. F. E. T.
 INPUT MULTIMETERS
 ■ ■ ■ POWER SUPPLIES,
 AND OTHER CUSTOM
 MADE ELECTRONIC
 INSTRUMENTS. ■ ■ ■

SPECIFICATIONS:	
SINE WAVES	1) From 1Hz to 1MHz frequency option continuously variable in 6 decades with overlapping ranges. 2) Output amplitude variable from 3mV to 10V peak-to-peak continuously variable.
OUTPUT IMPEDANCE	50 ohms nominal
SETTING ACCURACY	+/- 3% FSD +/- 1° for 1Hz to 100KHz ranges +/- 10% FSD +/- 1° for 100KHz to 1MHz ranges
SQUARE WAVE	1) From 1Hz to 1MHz frequency option continuously variable in 6 decades with overlapping ranges. 2) Output amplitude continuously variable from 50mV to 10V peak-to-peak.
SETTING ACCURACY	+/- 3% FSD +/- 1° for 10Hz to 100KHz ranges +/- 10% FSD +/- 1° for 100KHz to 1MHz ranges
SQUARE WAVE RISE TIME & FALL TIME BETTER THAN 70NSEC. POWER REQUIRED 230V, 50HZ & 7 WATTS.	
NOTE: WE RESERVE THE RIGHT TO ALTER THE SPECIFICATIONS FOR IMPROVEMENT OF THE PRODUCT.	

For details, please contact factory.